



# Unbeatable backwash valves Best performance, long service life



# WHAT MAKES OUR BACKWASH VALVES FROM PRAHER PLASTICS SO UNBEATABLE?

- More than 45 years of experience in development and production in Austria guarantee maximum precision.
- Top quality and durability are guaranteed through the use of excellent components.
- Millions have been tried and trusted in a wide range of climatic and technical conditions.
- Customer-specific adaptations such as laser engraving, glued piping components, colour variants and packaging leave nothing to be desired.
- Our own logistics centres in Europe and the Middle East ensure fast delivery times and considerable savings on logistical costs.
- We are so confident in our products that we offer a 10-year guarantee against housing breakage and a 10-year spare part delivery guarantee.



Nr.

1–3

(Side M.)

4–5

(Top M.)

## **BACKWASH VALVES**

### 7 position backwash valve V6 side mount 11/2", 2", 3"/top mount 11/2", 2" ABS PN3,5 and ASA GF PN6

### CHARACTERISTICS

- Easy handling
- Multi-lingual laser printing
- Optimal flow and pressure loss rates
- Extreme low-noise operation
- Made of high quality, UV resistant and impact resistant ABS materials
- High durable sealing material and pressure springs (installed on the valve plate)
- Pressure tightness and operation tests according to DIN 3230
- Easy installation on the  $\mathsf{AQUASTAR}^{\circledast}$  automatic backwash valve actuator
- Additional "winter position" for release of the sealing system



### 7 Positionen backwash valves V6 Side Mount 1 1/2", 2"

11/2" and 2" backwash valves with glued-in glued-in piping sets, suitable for all common filter brands, single packing, special piping solutions on request.



APPLICATION

Swimming pools, natural poosl, aquaristics, fish ponds and water

ASA GF swimming pools, sauna and spas with higher operation

Car wash and Smart pool applications by Aquastar adaption

attractions (fountains) for temperatures up to +40 °C

pressures and temperatures up to +50 °C

# INNOVATIVE HOUSING SEALING SYSTEM

Only 100 % original ABS high-tech material used, guaranteeing an aboveaverage service life.


# Where there's a will, there's a way

Finding ways has made us Austria's leading producer of pool equipment with a sound foundation of more than 45 years of experience in swimming pool and water treatment technology.

We are committed to providing products made of high-quality materials with components that work together perfectly, promising easy handling and maximum durability. For us, reliability starts with product development and ends with families enjoying more fun and leisure time together around their pool thanks to perfectly coordinated technology and first class quality.

PERAQUA: Your partner for smart pool automation and accessories.

PRESSURE LOSS DIAGRAM FILTER




A 11/2" Top-Mount TM 12-ND B 11/2" Side-Mount SM 10-ND C 2" Side-Mount SM 20 D 2" Top-Mount TM 22 E 3" Side-Mount SM 30-ND


 $\Delta \, p \, [bar]$ 

## **SIDE MOUNT**

	Dimensions 1 ½", 2" and 3"								
	1 1⁄2"		2"		3"				
	ABS	ASA-GF	ABS	ASA-GF	ABS	ASA-GF			
А	g	99	11	0	170				
В	18	30	22	27	329				
С	3′	1,5	36		50				
Е	48,5		60		85,5				
Е	60		81		110				
F	165		210		304				
G	247		296		434				
Н	41,5		36		50				
I	87,5		115		165				
К	17	175		230		330			
L	13	5,5	13	5,5	206				
М		-		-	-				
Х	3	30	3	6	50				
					D	imensions in mm			



#### Pipe connection 1 1⁄2" and 2" Ι from pump IV to pool Ш from filter V to waste ||| from filter











# **TOP MOUNT**


	Dimensions 1 ½" and 2"							
	11	2"	2"					
	ABS	ASA-GF	ABS	ASA-GF				
А	13	0	125					
В	see flange variations		see flange variations					
С	31	,5	36					
Е	3	8	43					
Е	59	,5	81					
F	235	5,5	280					
G	24	15	292					
Н	41,5		36					
Ι	90		114,5					
К	18	0	229					
L	135,5		135,5					
М	4	6	57					
Х	3	0	36					



Pipe connection 1½" and 2"							
Ι	bolt down flange						
Ш	threaded flange						
Ш	clamp flange with clamp ring set						



### PRESSURE LOSS DIAGRAM BACKWASH



Dimensions in mm

AQUASTARS®	
Aquastar® backwash valve easy 4001 (1 ½", 2")	Nr.
12–34 V AC/DC, 100–240 V AC (50-60Hz), time switch+pressure switch for fully automatic and cost-efficient backwash of filter systems	1
Aquastar® backwash valve MP PLC (1 ½", 2", 3")	Nr.
12–34 V AC/DC, 100–240 V AC (50-60Hz), excellent in combination with a PLC control, with ABS backwash valve (max. pressure 3,5 bar) or ASA-GF (max. pressure 5 bar) available, for fully automatic and cost-efficient back wash of filter systems	2
Aquastar® backwash valve comfort SafetyPack 12–34 V AC/DC, 100–240 V AC (50-60Hz), digital time control, for fully automatic and cost efficient backwashing of filter systems, for exclusive private as well as public pools and aquaparks where no external PLC control is available	Nr.
AQUASTAR® comfort 3001 (1 ½" 2", 3") with digital timer	3
AQUASTAR® comfort 3001 SafetyPack (1 ½", 2") with digital timer and SP safety accumulator	3
AQUASTAR <sup>®</sup> comfort 4001 (1 ½", 2", 3") with time and pressure switch	3
AQUASTAR® comfort 4001 SafetyPack (1 ½", 2") with time and pressure switch and SP safety accumulator	3
AQUASTAR® comfort 6501 (1 ½", 2", 3") with 2-channel-timer and pressure switch	3
AQUASTAR® comfort 6501 SafetyPack (1 ½", 2") with 2-channel-timer, pressure switch and SP safety accumulator	3

# **MODIFICATION OF MANUAL PRAHER V6 VALVES TO** MODERN, FULLY AUTOMATIC BACKWASHING USING THE AQUASTAR® SERIES



# **ACCESSORIES**

Deliverable also in black and gray (on request). Dimensions: d50, d63, at adapter unions: d50, d63, d90

Valve piping set PENTAIR



Valve piping set ASTRAL, ESPA, MMC, CERTIKIN

Valve piping set HAYWARD



Elbow and connection piece Ocean<sup>®</sup> union





pooled family pleasure

### HEAD QUARTER AND EXPORT

Peraqua Professional Water Products GmbH Handelsstraße 8 4300 St. Valentin

T. +43 7435/58488-0 F. +43 7435/58488-2009

info@peraqua.com www.peraqua.com



### SALES, LOGISTICS AND TECHNICS

0

PERAPLAS DEUTSCHLAND GMBH Regensburger Ring 12, 91154 Roth T. +49 9171 9677-1200, F. +49 9171 9677-2209 office.de@peraplas.com

PERAPLAS ČESKO s.r.o. 25101 Říčany-Jažlovice, Zděbradská 62 T. +420 323 63 76-73, F. +420 323 63 76-72 office.cz@peraplas.com

PERAPLAS Praher Middle East FZE PO Box No. 122435, Plot No. 04-99, SAIF Zone, Sharjah, UAE T. +971-6-557 98 66, F. +971-6-557 97 07 office.ae@peraplas.com

Member of GROUP

0

0

õ

20

0